

Soluzioni Innovative per la Ricostruzione delle Componenti Radianti della Sorgente Equivalente in Problemi di Scattering Elettromagnetico Inverso

D. De Guidi

Abstract

Nell'ambito delle tecniche sviluppate per problemi di scattering elettromagnetico o inverso, varie metodologie considerano l'introduzione di una densità di corrente equivalente nel dominio di indagine che si vuole ricostruire (approccio "inverse source").

Tale sorgente equivalente è caratterizzata da componenti radianti (o a minima norma) di cui il campo scatterato porta informazione e da componenti non-radianti, difficili da ricostruire. Varie metodologie sono state presentate per la ricostruzione delle componenti della sorgente equivalente, solitamente attraverso l'implementazione di procedure a 2 passi [1][2], dove al primo passo si definiscono le correnti a minima norma, mentre al secondo le correnti non-radianti.

Benché la maggior parte delle metodologie presentate in questo ambito riguardino principalmente la ricostruzione della parte non-radiante, un problema che può ridurre l'efficacia dell'inversione risiede nella non accurata definizione delle correnti radianti ottenute partendo dai dati di campo scatterato. L'argomento del presente lavoro di tesi considera l'integrazione di relazioni analitiche [3] per la definizione della sorgente equivalente a minima norma nell'approccio proposto in [2] per la ricostruzione delle sorgenti non-radianti.

References Bibliography: Inverse Scattering [1] – [19].

- [1] S. C. Hagness, E. C. Fear, and A. Massa, "Guest Editorial: Special Cluster on Microwave Medical Imaging", *IEEE Antennas Wireless Propag. Lett.*, vol. 11, pp. 1592-1597, 2012.
- [2] G. Oliveri, Y. Zhong, X. Chen, and A. Massa, "Multi-resolution subspace-based optimization method for inverse scattering," *Journal of Optical Society of America A*, vol. 28, no. 10, pp. 2057-2069, Oct. 2011.
- [3] A. Randazzo, G. Oliveri, A. Massa, and M. Pastorino, "Electromagnetic inversion with the multiscaling inexact-Newton method - Experimental validation," *Microwave Opt. Technol. Lett.*, vol. 53, no. 12, pp. 2834-2838, Dec. 2011.
- [4] G. Oliveri, L. Lizzi, M. Pastorino, and A. Massa, "A nested multi-scaling inexact-Newton iterative approach for microwave imaging," *IEEE Trans. Antennas Propag.*, vol. 60, no. 2, pp. 971-983, Feb. 2012.
- [5] G. Oliveri, A. Randazzo, M. Pastorino, and A. Massa, "Electromagnetic imaging within the contrast-source formulation by means of the multiscaling inexact Newton method," *Journal of Optical Society of America A*, vol. 29, no. 6, pp. 945-958, 2012.

- [6] M. Benedetti, D. Lesselier, M. Lambert, and A. Massa, "Multiple shapes reconstruction by means of multi-region level sets," *IEEE Trans. Geosci. Remote Sensing*, vol. 48, no. 5, pp. 2330-2342, May 2010.
- [7] M. Benedetti, D. Lesselier, M. Lambert, and A. Massa, "A multi-resolution technique based on shape optimization for the reconstruction of homogeneous dielectric objects," *Inverse Problems*, vol. 25, no. 1, pp. 1-26, Jan. 2009.
- [8] M. Donelli, D. Franceschini, P. Rocca, and A. Massa, "Three-dimensional microwave imaging problems solved through an efficient multi-scaling particle swarm optimization," *IEEE Trans. Geosci. Remote Sensing*, vol. 47, no. 5, pp. 1467-1481, May 2009.
- [9] M. Benedetti, G. Franceschini, R. Azaro, and A. Massa, "A numerical assessment of the reconstruction effectiveness of the integrated GA-based multicrack strategy," *IEEE Antennas Wireless Propag. Lett.*, vol. 6, pp. 271-274, 2007.
- [10] P. Rocca, M. Carlin, G. Oliveri, and A. Massa, "Interval analysis as applied to inverse scattering," *IEEE International Symposium on Antennas Propag. (APS/URSI 2013)*, Chicago, Illinois, USA, Jul. 8-14, 2012.
- [11] L. Manica, P. Rocca, M. Salucci, M. Carlin, and A. Massa, "Scattering data inversion through interval analysis under Rytov approximation," *7th European Conference on Antennas Propag. (EuCAP 2013)*, Gothenburg, Sweden, Apr. 8-12, 2013.
- [12] P. Rocca, M. Carlin, and A. Massa, "Imaging weak scatterers by means of an innovative inverse scattering technique based on the interval analysis," *6th European Conference on Antennas Propag. (EuCAP 2012)*, Prague, Czech Republic, Mar. 26-30, 2012.
- [13] L. Poli, G. Oliveri, and A. Massa, "Imaging sparse metallic cylinders through a Local Shape Function Bayesian Compressive Sensing approach," *Journal of Optical Society of America A*, vol. 30, no. 6, pp. 1261-1272, 2013.
- [14] F. Viani, L. Poli, G. Oliveri, F. Robol, and A. Massa, "Sparse scatterers imaging through approximated multitask compressive sensing strategies," *Microwave Opt. Technol. Lett.*, vol. 55, no. 7, pp. 1553-1558, Jul. 2013.
- [15] L. Poli, G. Oliveri, P. Rocca, and A. Massa, "Bayesian compressive sensing approaches for the reconstruction of two-dimensional sparse scatterers under TE illumination," *IEEE Trans. Geosci. Remote Sensing*, vol. 51, no. 5, pp. 2920-2936, May. 2013.
- [16] L. Poli, G. Oliveri, and A. Massa, "Microwave imaging within the first-order Born approximation by means of the contrast-field Bayesian compressive sensing," *IEEE Trans. Antennas Propag.*, vol. 60, no. 6, pp. 2865-2879, Jun. 2012.
- [17] G. Oliveri, P. Rocca, and A. Massa, "A bayesian compressive sampling-based inversion for imaging sparse scatterers," *IEEE Trans. Geosci. Remote Sensing*, vol. 49, no. 10, pp. 3993-4006, Oct. 2011.
- [18] G. Oliveri, L. Poli, P. Rocca, and A. Massa, "Bayesian compressive optical imaging within the Rytov approximation," *Optics Letters*, vol. 37, no. 10, pp. 1760-1762, 2012.
- [19] L. Poli, G. Oliveri, F. Viani, and A. Massa, "MT-BCS-based microwave imaging approach through minimum-norm current expansion," *IEEE Trans. Antennas Propag.*, in press. doi: 10.1109/TAP.2013.2265254.

This report is submitted in partial fulfillment of the degree of the course "TDB".

Supervisors: Prof. A. Massa, Dr. P. Rocca.