

Multiresolution subspace-based optimization method for three-dimensional inverse scattering problems

M. Bertoluzza

Abstract

Nell'ambito delle tecniche sviluppate per problemi di scattering elettromagnetico inverso, varie metodologie considerano l'introduzione di una densità di corrente equivalente nel dominio di indagine che si vuole ricostruire (approccio inverse source). Tale sorgente equivalente è caratterizzata da componenti radianti (o a minima norma) di cui il campo scatterato porta informazione e da componenti debolmente radianti o non-radianti, che non possono essere ricostruite facilmente. In tale ambito, sono state proposte varie metodologie per la ricostruzione delle componenti della sorgente equivalente, solitamente attraverso l'implementazione di procedure a 2 passi, dove al primo passo si definiscono le correnti "a minima norma", mentre al secondo le correnti "ambigue".

In tale ambito, è stato recentemente introdotto un approccio efficace di soluzione di tale problema basato sul Subspace Optimization Method (SOM). Tale approccio definisce un funzionale di costo con termini misti (sia relativi all'equazione di stato che all'equazione dei dati). La sua efficacia è stata inoltre incrementata mediante la sua integrazione con metodologie multi-risoluzione, in grado di mitigare i problemi di minimi locali derivanti dall'utilizzo di tecniche di tipo "gradiente" per il calcolo delle componenti ambigue della corrente equivalente.

Scopo della presente attività è l'analisi della metodologia IMSA-SOM per il caso three-dimensional imaging.

Reference Bibliography: Inverse Scattering [1]-[19].

- [1] S. C. Hagness, E. C. Fear, and A. Massa, "Guest Editorial: Special Cluster on Microwave Medical Imaging", *IEEE Antennas Wireless Propag. Lett.*, vol. 11, pp. 1592-1597, 2012.
- [2] G. Oliveri, Y. Zhong, X. Chen, and A. Massa, "Multi-resolution subspace-based optimization method for inverse scattering," *Journal of Optical Society of America A*, vol. 28, no. 10, pp. 2057-2069, Oct. 2011.
- [3] A. Randazzo, G. Oliveri, A. Massa, and M. Pastorino, "Electromagnetic inversion with the multiscaling inexact-Newton method - Experimental validation," *Microwave Opt. Technol. Lett.*, vol. 53, no. 12, pp. 2834-2838, Dec. 2011.
- [4] G. Oliveri, L. Lizzi, M. Pastorino, and A. Massa, "A nested multi-scaling inexact-Newton iterative approach for microwave imaging," *IEEE Trans. Antennas Propag.*, vol. 60, no. 2, pp. 971-983, Feb. 2012.
- [5] G. Oliveri, A. Randazzo, M. Pastorino, and A. Massa, "Electromagnetic imaging within the contrast-source formulation by means of the multiscaling inexact Newton method," *Journal of Optical Society of America A*, vol. 29, no. 6, pp. 945-958, 2012.

- [6] M. Benedetti, D. Lesselier, M. Lambert, and A. Massa, "Multiple shapes reconstruction by means of multi-region level sets," *IEEE Trans. Geosci. Remote Sensing*, vol. 48, no. 5, pp. 2330-2342, May 2010.
- [7] M. Benedetti, D. Lesselier, M. Lambert, and A. Massa, "A multi-resolution technique based on shape optimization for the reconstruction of homogeneous dielectric objects," *Inverse Problems*, vol. 25, no. 1, pp. 1-26, Jan. 2009.
- [8] M. Donelli, D. Franceschini, P. Rocca, and A. Massa, "Three-dimensional microwave imaging problems solved through an efficient multi-scaling particle swarm optimization," *IEEE Trans. Geosci. Remote Sensing*, vol. 47, no. 5, pp. 1467-1481, May 2009.
- [9] M. Benedetti, G. Franceschini, R. Azaro, and A. Massa, "A numerical assessment of the reconstruction effectiveness of the integrated GA-based multicrack strategy," *IEEE Antennas Wireless Propag. Lett.*, vol. 6, pp. 271-274, 2007.
- [10] P. Rocca, M. Carlin, G. Oliveri, and A. Massa, "Interval analysis as applied to inverse scattering," *IEEE International Symposium on Antennas Propag. (APS/URSI 2013)*, Chicago, Illinois, USA, Jul. 8-14, 2012.
- [11] L. Manica, P. Rocca, M. Salucci, M. Carlin, and A. Massa, "Scattering data inversion through interval analysis under Rytov approximation," *7th European Conference on Antennas Propag. (EuCAP 2013)*, Gothenburg, Sweden, Apr. 8-12, 2013.
- [12] P. Rocca, M. Carlin, and A. Massa, "Imaging weak scatterers by means of an innovative inverse scattering technique based on the interval analysis," *6th European Conference on Antennas Propag. (EuCAP 2012)*, Prague, Czech Republic, Mar. 26-30, 2012.
- [13] L. Poli, G. Oliveri, and A. Massa, "Imaging sparse metallic cylinders through a Local Shape Function Bayesian Compressive Sensing approach," *Journal of Optical Society of America A*, vol. 30, no. 6, pp. 1261-1272, 2013.
- [14] F. Viani, L. Poli, G. Oliveri, F. Robol, and A. Massa, "Sparse scatterers imaging through approximated multitask compressive sensing strategies," *Microwave Opt. Technol. Lett.*, vol. 55, no. 7, pp. 1553-1558, Jul. 2013.
- [15] L. Poli, G. Oliveri, P. Rocca, and A. Massa, "Bayesian compressive sensing approaches for the reconstruction of two-dimensional sparse scatterers under TE illumination," *IEEE Trans. Geosci. Remote Sensing*, vol. 51, no. 5, pp. 2920-2936, May. 2013.
- [16] L. Poli, G. Oliveri, and A. Massa, "Microwave imaging within the first-order Born approximation by means of the contrast-field Bayesian compressive sensing," *IEEE Trans. Antennas Propag.*, vol. 60, no. 6, pp. 2865-2879, Jun. 2012.
- [17] G. Oliveri, P. Rocca, and A. Massa, "A bayesian compressive sampling-based inversion for imaging sparse scatterers," *IEEE Trans. Geosci. Remote Sensing*, vol. 49, no. 10, pp. 3993-4006, Oct. 2011.
- [18] G. Oliveri, L. Poli, P. Rocca, and A. Massa, "Bayesian compressive optical imaging within the Rytov approximation," *Optics Letters*, vol. 37, no. 10, pp. 1760-1762, 2012.
- [19] L. Poli, G. Oliveri, F. Viani, and A. Massa, "MT-BCS-based microwave imaging approach through minimum-norm current expansion," *IEEE Trans. Antennas Propag.*, in press.
doi:10.1109/TAP.2013.2265254

*This report is submitted in partial fulfillment of the degree of the course "TDB".
Supervisors: Prof. Andrea Massa, Dr. Lorenzo Poli.*