

# **Subsurface imaging basato su approccio IMSA-Inexact Newton [Cross-Well]**

A. Tommasi

## **Abstract**

L'analisi non invasiva e non distruttiva di materiali e strutture rappresenta un argomento di grande importanza per le applicazioni di introspezione sottosuperficiale non distruttiva. In tale ambito, sono state proposte numerose metodologie in grado di gestire efficacemente la non-linearità/mal posizione dei problemi inversi risultanti. In particolare, è stata recentemente proposta una metodologia integrata per la linearizzazione/regolarizzazione del problema inverso, denominata IMSA-Inexact Newton Method, in grado di fornire efficaci prestazioni anche in presenza di forti scatteratori e di dati distorti significativamente dal rumore. Per tale ragione, risulta di interesse l'analisi delle prestazioni di tale metodologia quando applicata a problemi di subsurface imaging, nei quali i dati a disposizione sono spesso fortemente disturbati e gli oggetti da rilevare sono caratterizzati da costanti dielettriche elevate.

Date le precedenti osservazioni, obiettivo dell'attività è perciò l'indagine delle potenzialità dell'approccio integrato multiscaling-Inexact Newton per applicazioni di introspezione sottosuperficiale. In tale attività si farà riferimento in modo specifico a dati raccolti in configurazione "cross-well", cioè in presenza di sensori inseriti nel terreno.

**Reference Bibliography:** Inverse Scattering [1]-[19].

- [1] S. C. Hagness, E. C. Fear, and A. Massa, "Guest Editorial: Special Cluster on Microwave Medical Imaging", IEEE Antennas Wireless Propag. Lett., vol. 11, pp. 1592-1597, 2012.
- [2] G. Oliveri, Y. Zhong, X. Chen, and A. Massa, "Multi-resolution subspace-based optimization method for inverse scattering," Journal of Optical Society of America A, vol. 28, no. 10, pp. 2057-2069, Oct. 2011.
- [3] A. Randazzo, G. Oliveri, A. Massa, and M. Pastorino, "Electromagnetic inversion with the multiscaling inexact-Newton method - Experimental validation," Microwave Opt. Technol. Lett., vol. 53, no. 12, pp. 2834-2838, Dec. 2011.
- [4] G. Oliveri, L. Lizzi, M. Pastorino, and A. Massa, "A nested multi-scaling inexact-Newton iterative approach for microwave imaging," IEEE Trans. Antennas Propag., vol. 60, no. 2, pp. 971-983, Feb. 2012.
- [5] G. Oliveri, A. Randazzo, M. Pastorino, and A. Massa, "Electromagnetic imaging within the contrast-source formulation by means of the multiscaling inexact Newton method," Journal of Optical Society of America A, vol. 29, no. 6, pp. 945-958, 2012.
- [6] M. Benedetti, D. Lesselier, M. Lambert, and A. Massa, "Multiple shapes reconstruction by means of multi-region level sets," IEEE Trans. Geosci. Remote Sensing, vol. 48, no. 5, pp. 2330-2342, May 2010.

- [7] M. Benedetti, D. Lesselier, M. Lambert, and A. Massa, "A multi-resolution technique based on shape optimization for the reconstruction of homogeneous dielectric objects," *Inverse Problems*, vol. 25, no. 1, pp. 1-26, Jan. 2009.
- [8] M. Donelli, D. Franceschini, P. Rocca, and A. Massa, "Three-dimensional microwave imaging problems solved through an efficient multi-scaling particle swarm optimization," *IEEE Trans. Geosci. Remote Sensing*, vol. 47, no. 5, pp. 1467-1481, May 2009.
- [9] M. Benedetti, G. Franceschini, R. Azaro, and A. Massa, "A numerical assessment of the reconstruction effectiveness of the integrated GA-based multicrack strategy," *IEEE Antennas Wireless Propag. Lett.*, vol. 6, pp. 271-274, 2007.
- [10] P. Rocca, M. Carlin, G. Oliveri, and A. Massa, "Interval analysis as applied to inverse scattering," *IEEE International Symposium on Antennas Propag. (APS/URSI 2013)*, Chicago, Illinois, USA, Jul. 8-14, 2012.
- [11] L. Manica, P. Rocca, M. Salucci, M. Carlin, and A. Massa, "Scattering data inversion through interval analysis under Rytov approximation," *7th European Conference on Antennas Propag. (EuCAP 2013)*, Gothenburg, Sweden, Apr. 8-12, 2013.
- [12] P. Rocca, M. Carlin, and A. Massa, "Imaging weak scatterers by means of an innovative inverse scattering technique based on the interval analysis," *6th European Conference on Antennas Propag. (EuCAP 2012)*, Prague, Czech Republic, Mar. 26-30, 2012.
- [13] L. Poli, G. Oliveri, and A. Massa, "Imaging sparse metallic cylinders through a Local Shape Function Bayesian Compressive Sensing approach," *Journal of Optical Society of America A*, vol. 30, no. 6, pp. 1261-1272, 2013.
- [14] F. Viani, L. Poli, G. Oliveri, F. Robol, and A. Massa, "Sparse scatterers imaging through approximated multitask compressive sensing strategies," *Microwave Opt. Technol. Lett.*, vol. 55, no. 7, pp. 1553-1558, Jul. 2013.
- [15] L. Poli, G. Oliveri, P. Rocca, and A. Massa, "Bayesian compressive sensing approaches for the reconstruction of two-dimensional sparse scatterers under TE illumination," *IEEE Trans. Geosci. Remote Sensing*, vol. 51, no. 5, pp. 2920-2936, May. 2013.
- [16] L. Poli, G. Oliveri, and A. Massa, "Microwave imaging within the first-order Born approximation by means of the contrast-field Bayesian compressive sensing," *IEEE Trans. Antennas Propag.*, vol. 60, no. 6, pp. 2865-2879, Jun. 2012.
- [17] G. Oliveri, P. Rocca, and A. Massa, "A bayesian compressive sampling-based inversion for imaging sparse scatterers," *IEEE Trans. Geosci. Remote Sensing*, vol. 49, no. 10, pp. 3993-4006, Oct. 2011.
- [18] G. Oliveri, L. Poli, P. Rocca, and A. Massa, "Bayesian compressive optical imaging within the Rytov approximation," *Optics Letters*, vol. 37, no. 10, pp. 1760-1762, 2012.
- [19] L. Poli, G. Oliveri, F. Viani, and A. Massa, "MT-BCS-based microwave imaging approach through minimum-norm current expansion," *IEEE Trans. Antennas Propag.*, in press.  
doi:10.1109/TAP.2013.2265254

*This report is submitted in partial fulfillment of the degree of the course "DCM".  
Supervisors: Prof. Andrea Massa, Dr. Giacomo Oliveri.*